



BAGNOTHERM BT75-2

Visina 726 mm

Model	BT75-2						
Visina H [mm]	726						
Dubina T [mm]	70						
Dužina L [mm]	450	500	550	600	750	900	
Oсно ostojanje N [mm]	385	435	485	535	685	835	
$\Phi_S \Delta T 50K$ -Toplinski učinak [Watt]	509	563	616	670	830	991	
Težina [kg]	13,6	14,9	16,3	17,6	21,6	25,6	
Volumen [dm ³]	6,2	6,8	7,6	8,2	10,3	12,3	
Standardni protok Qms [kg/h]	43,8	48,4	53,0	57,6	71,4	85,2	
[%]	25	25	25	25	25	25	
Exponent n [Exp]	1,28	1,27	1,26	1,25	1,23	1,20	
AF 6- Bijela boja RAL 9016 [KN]	3.153,00	3.224,00	3.294,00	3.365,00	3.570,00	3.731,00	
CF - Boja po izboru [KN]	3.784,00	3.866,00	3.953,00	4.038,00	4.284,00	4.538,00	
SF [KN]	4.099,00	4.193,00	4.283,00	4.375,00	4.641,00	4.916,00	
Odgovarajući elekt.grijač [Watt/A]	500 / 3	500 / 3	500 / 3	800 / 4	800 / 4	1100 / 5	

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

BAGNOTHERM BT115-2

Visina 1144 mm

Model	BT115-2						
Visina H [mm]	1144						
Dubina T [mm]	70						
Dužina L [mm]	450	500	550	600	750	900	
Oсно ostojanje N [mm]	385	435	485	535	685	835	
$\Phi_S \Delta T 50K$ -Toplinski učinak [Watt]	736	825	914	1004	1278	1556	
Težina [kg]	20,8	22,8	24,8	26,9	32,9	39,0	
Volumen [dm ³]	9,6	10,6	11,6	12,7	15,7	18,8	
Standardni protok Qms [kg/h]	63,3	70,9	78,6	86,3	109,9	133,8	
[%]	25	25	25	25	25	25	
Exponent n [Exp]	1,25	1,26	1,22	1,21	1,18	1,14	
AF 6- Bijela boja RAL 9016 [KN]	4.085,00	4.190,00	4.289,00	4.395,00	4.713,00	5.037,00	
CF - Boja po izboru [KN]	4.902,00	5.029,00	5.147,00	5.274,00	5.655,00	6.045,00	
SF [KN]	5.310,00	5.448,00	5.576,00	5.714,00	6.127,00	6.548,00	
Odgovarajući elekt.grijač [Watt/A]	800 / 4	800 / 4	800 / 4	1100 / 5	1100 / 5	1500 / 7	

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:



BAGNOTHERM BT150-2

Visina 1486 mm

Model		BT150-2					
Visina H	[mm]	1486					
Dubina T	[mm]	70					
Dužina L	[mm]	450	500	550	600	750	900
Oсно ostojanje N	[mm]	385	435	485	535	685	835
$\Phi_S \Delta T 50K$ -Toplinski učinak	[Watt]	946	1060	1175	1291	1642	2000
Težina	[kg]	27,9	30,6	33,3	36,0	44,2	52,3
Volumen	[dm ³]	13,0	14,4	15,8	17,2	21,4	25,6
Standardni protok Qms	[kg/h]	81,3	91,1	101,0	111,0	141,2	172,0
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,29	1,28	1,27	1,26	1,24	1,22
AF 6- Bijela boja RAL 9016	[KUN]	4.995,00	5.143,00	5.284,00	5.425,00	5.856,00	6.279,00
CF - Boja po izboru	[KUN]	5.994,00	6.172,00	6.341,00	6.510,00	7.027,00	7.535,00
SF	[KUN]	6.493,00	6.686,00	6.869,00	7.053,00	7.612,00	8.163,00
SL	[KUN]	5.994,00	6.172,00	6.341,00	6.510,00	7.027,00	7.535,00
KL	[KUN]	6.493,00	6.686,00	6.869,00	7.053,00	7.612,00	8.163,00
ZN	[KUN]	10.794,00	11.503,00	12.206,00	12.905,00	15.043,00	17.150,00
ZL	[KUN]	11.793,00	12.532,00	13.263,00	13.993,00	16.214,00	18.406,00
ZK	[KUN]	12.293,00	13.046,00	13.791,00	14.536,00	16.800,00	19.034,00
Odgovarajući elekt.grijač	[Watt/A]	800 / 4	1100 / 5	1100 / 5	1100 / 5	1500 / 7	–

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442) $\Delta T 50K$:

BAGNOTHERM BT180-2

Height 1790 mm

Model		BT180-2					
Visina H	[mm]	1790					
Dubina T	[mm]	70					
Dužina L	[mm]	450	500	550	600	750	900
Oсно odstojanje N	[mm]	385	435	485	535	685	835
$\Phi_S \Delta T 50K$ -Toplinski učinak	[Watt]	1123	1258	1395	1532	1950	2375
Težina	[kg]	27,9	30,6	33,3	36,0	44,2	52,3
Volumen	[dm ³]	13,0	14,4	15,8	17,2	21,4	25,6
Standardni protok Qms	[kg/h]	96,6	108,2	119,9	131,7	167,7	204,2
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,28	1,28	1,27	1,27	1,25	1,24
AF 6- Bijela boja RAL 9016	[KUN]	5.623,00	5.792,00	5.954,00	6.124,00	6.625,00	7.123,00
CF - Boja po izboru	[KUN]	6.747,00	6.951,00	7.145,00	7.349,00	7.950,00	8.551,00
SF	[KUN]	7.310,00	7.530,00	7.741,00	7.961,00	8.612,00	9.236,00
Odgovarajući elekt.grijač	[Watt/A]	1100 / 5	1100 / 5	1500 / 7	1500 / 7	–	–

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442) $\Delta T 50K$: