



BAGNOTHERM FLEX BTf75

Visina 726 mm

RADIJATOR ZA BOČNI PRIKLJUČAK - VARIJABILNO

		BTf75					
Model							
Visina H	[mm]	726					
Dubina T	[mm]	49					
Dužina L	[mm]	450	500	550	600	750	900
Osovo ostojanje N	[mm]	varijabilno					
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	343	385	428	471	602	735
Težina	[kg]	7,5	8,2	8,9	9,5	11,6	13,6
Volumen	[dm ³]	3,5	3,8	4,2	4,5	5,5	6,5
Standardni protok Qms	[kg/h]	29,5	33,1	36,8	40,5	51,8	63,2
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,25	1,24	1,24	1,23	1,20	1,18
AF 6- Bijela boja RAL 9016	[KN]	2.483,00	2.504,00	2.532,00	2.568,00	2.652,00	2.737,00
CF - Boja po izboru	[KN]	2.895,00	2.920,00	2.954,00	2.997,00	3.098,00	3.200,00
SF	[KN]	3.101,00	3.129,00	3.165,00	3.211,00	3.321,00	3.431,00
CROM	[KN]	4.487,00	4.755,00	5.016,00	5.291,00	6.131,00	6.907,00
P_{el}/I Odgovarajući elekt. grijač	[Watt/A]	500 / 3	500 / 3	500 / 3	500 / 3	500 / 3	800 / 4

$\Phi_S \Delta T 50K$: Za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

BAGNOTHERM FLEX BTf115

Visina 1144 mm

RADIJATOR ZA BOČNI PRIKLJUČAK - VARIJABILNO

		BTf115					
Model							
Visina H	[mm]	1144					
Dubina T	[mm]	49					
Dužina L	[mm]	450	500	550	600	750	900
Osovo ostojanje N	[mm]	varijabilno					
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	523	588	653	718	918	1122
Težina	[kg]	11,5	12,5	13,5	14,6	17,6	20,7
Volumen	[dm ³]	5,4	5,9	6,4	7,0	8,5	10,1
Standardni protok Qms	[kg/h]	45,0	50,6	56,1	61,7	78,9	96,5
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,25	1,26	1,22	1,21	1,18	1,14
AF 6- Bijela boja RAL 9016	[KN]	2.949,00	2.991,00	3.033,00	3.083,00	3.210,00	3.344,00
CF - Boja po izboru	[KN]	3.454,00	3.505,00	3.555,00	6.615,00	3.767,00	3.928,00
SF	[KN]	3.706,00	3.761,00	3.817,00	3.881,00	4.046,00	4.220,00
CROM	[KN]	6.413,00	6.745,00	7.182,00	7.612,00	8.932,00	10.244,00
P_{el}/I Odgovarajući elekt. grijač	[Watt/A]	500 / 3	500 / 3	800 / 4	800 / 4	800 / 4	1100 / 5

$\Phi_S \Delta T 50K$: Za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

**BAGNOTHERM FLEX BTF150**

Visina 1486 mm

RADIJATOR ZA BOČNI PRIKLJUČAK - VARIJABILNO

Model		BTF150					
Visina H	[mm]	1486					
Dubina T	[mm]	49					
Dužina L	[mm]	450	500	550	600	750	900
Osovo odstojanje polaz/povrat N	[mm]	varijabilno					
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	670	752	836	920	1175	1436
Težina M	[kg]	15,5	16,9	18,2	19,6	23,7	27,8
Volumen V	[dm ³]	7,1	7,8	8,5	9,1	11,2	13,2
Standardni protok Qms	[kg/h]	57,6	64,7	71,9	79,1	101,0	123,5
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,26	1,25	1,24	1,23	1,20	1,16
AF 6- Bijela boja RAL 9016	[KN]	3.407,00	3.471,00	3.527,00	3.591,00	3.767,00	3.944,00
CF- Boja po izboru	[KN]	4.004,00	4.080,00	4.148,00	4.224,00	4.436,00	4.648,00
SF	[KN]	4.303,00	4.385,00	4.459,00	4.541,00	4.770,00	5.000,00
CROM	[KN]	7.500,00	8.007,00	8.544,00	9.073,00	10.653,00	12.276,00
Odgovarajući Elektro grijač	[Watt/A]	800 / 4	800 / 4	800 / 4	800 / 4	1100 / 5	1500 / 7

 $\Phi_S \Delta T 50K$: Za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442) $\Delta T 50K$:**BAGNOTHERM FLEX BTF180**

Visina 1790 mm

RADIJATOR ZA BOČNI PRIKLJUČAK - VARIJABILNO

Model		BTF180					
Visina H	[mm]	1790					
Dubina T	[mm]	49					
Dužina L	[mm]	450	500	550	600	750	900
Osovo odstojanje N	[mm]	varijabilno					
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	839	926	1013	1100	1360	1620
Težina	[kg]	18,4	20,0	21,6	23,2	27,9	32,7
Volumen	[dm ³]	8,0	8,8	9,7	10,5	13,1	15,6
Standardni protok Qms	[kg/h]	72,1	79,6	87,1	94,6	116,9	139,3
	[%]	25	25	25	25	25	25
Exponent n	[Exp]	1,27	1,25	1,24	1,23	1,19	1,15
AF 6- Bijela boja RAL 9016	[KN]	3.725,00	3.802,00	3.866,00	3.936,00	4.141,00	4.353,00
CF - Boja po izboru	[KN]	4.385,00	4.478,00	4.555,00	4.639,00	4.885,00	5.139,00
SF	[KN]	4.715,00	4.816,00	4.899,00	4.991,00	5.257,00	5.532,00
CROM	[KN]	8.558,00	9.122,00	9.743,00	10.371,00	12.241,00	14.068,00
Odgovarajući Elektro grijač	[Watt/A]	800 / 4	800 / 4	1100 / 5	1100 / 5	1500 / 7	1500 / 7

 $\Phi_S \Delta T 50K$: Za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442) $\Delta T 50K$: