



BAGNOTHERM MOVE BTM75 L/R

Visina 726 mm

Model		BTM75 L/R
Visina H	[mm]	726
Dubina T	[mm]	49
Dužina L	[mm]	500
Oсно ostojanje N	[mm]	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	441
Težina	[kg]	8,5
Volumen	[dm ³]	3,5
Standardni protok Qms	[kg/h]	37,9
	[%]	25
Exponent n	[Exp]	1,24
AF 6- Bijela boja RAL 9016	[KN]	2.716,00
CF - Boja po izboru	[KN]	3.259,00
SF	[KN]	3.531,00
CROM	[KN]	5.270,00
P _{el} /I odgovarajući grijač	[Watt/A]	500 / 3

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

Dužine 750 mm na upit !

BAGNOTHERM MOVE BTM115 L/R

Visina 1144 mm

Model		BTM115 L/R	
Visina H	[mm]	1144	
Dubina T	[mm]	49	
Dužina L	[mm]	500	600
Oсно ostojanje N	[mm]	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	622	775
Težina	[kg]	12,8	14,8
Volumen	[dm ³]	5,5	6,5
Standardni protok Qms	[kg/h]	53,5	66,6
	[%]	25	25
Exponent n	[Exp]	1,23	1,23
AF 6- Bijela boja RAL 9016	[KN]	3.252,00	3.344,00
CF - Boja po izboru	[KN]	3.903,00	4.013,00
SF	[KN]	4.228,00	4.347,00
CROM	[KN]	7.556,00	8.480,00
P _{el} /I Odgovarajući greijač	[Watt/A]	500 / 3	800 / 4

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

Dužine 750 mm na upit !


BAGNOTHERM MOVE BTM150 L/R

Visina 1488 mm

Model		BTM150 L/R	
Visina H	[mm]	1488	
Dubina T	[mm]	49	
Dužina L	[mm]	500	600
Oсно ostojanje N	[mm]	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	793	974
Težina	[kg]	17,4	20,0
Volumen	[dm ³]	6,6	8,2
Standardni protok Qms	[kg/h]	68,2	83,7
	[%]	25	25
Exponent n	[Exp]	1,21	1,22
AF 6- Bijela boja RAL 9016	[KN]	3.894,00	4.014,00
CF	[KN]	4.673,00	4.817,00
SF	[KN]	5.063,00	5.218,00
CROM	[KN]	9.101,00	10.230,00
P _{el} /I Odgovarajući grijač	[Watt/A]	800 / 4	1100 / 5

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

 $\Delta T 50K$:

Dužina 750 mm na upit !

BAGNOTHERM MOVE BTM180 L/R

Visina 1790 mm

Model		BTM180 L/R		
Visina H	[mm]	1790		
Dubina T	[mm]	49		
Dužina L	[mm]	500	600	750
Oсно ostojanje N	[mm]	50	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	959	1147	1429
Težina	[kg]	20,7	23,8	28,4
Volumen	[dm ³]	8,2	9,8	12,2
Standardni protok Qms	[kg/h]	82,5	98,6	122,9
	[%]	25	25	25
Exponent n	[Exp]	1,19	1,21	1,24
AF 6- Bijela boja RAL 9016	[KN]	4.169,00	4.261,00	4.353,00
CF - Boja po izboru	[KN]	5.003,00	5.113,00	5.223,00
SF	[KN]	5.420,00	5.539,00	5.659,00
CROM	[KN]	10.406,00	11.571,00	13.687,00
P _{el} /I Odgovarajući grijač	[Watt/A]	1100 / 5	1100 / 5	1500 / 7

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

 $\Delta T 50K$: