



COBRATHERM CBT110 L/R

Visina 1100 mm

Model		CBT110 L/R		
Visina H	[mm]	1100		
Dubina T	[mm]	58		
Dužina L	[mm]	400	500	600
Oсно odstojanje N	[mm]	50	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	344	408	474
Težina	[kg]	6,1	7,1	8,1
Volumen	[dm ³]	2,5	2,8	3,1
Standardni protok Qms	[kg/h]	29,6	35,2	40,8
	[%]	25	25	25
Exponent n	[Exp]	1,24	1,25	1,26
AF 6- Bijela boja RAL 9016	[KN]	2.656,00	2.699,00	2.734,00
CF - Boja po izboru	[KN]	3.187,00	3.239,00	3.280,00
SF	[KN]	3.452,00	3.509,00	3.554,00
CROM	[KN]	6.713,00	7.172,00	7.631,00
Odgovarajući elekt. grijač	[Watt/A]	500 / 3	500 / 3	500 / 3

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

COBRATHERM CBT140 L/R

Visina 1400 mm

Model		CBT140 L/R		
Visina H	[mm]	1400		
Dubina T	[mm]	58		
Dužina L	[mm]	400	500	600
Oсно odstojanje N	[mm]	50	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak	[Watt]	445	533	620
Težina	[kg]	7,8	9,1	10,3
Volumen	[dm ³]	3,1	3,5	3,9
Standardni protok Qms	[kg/h]	38,4	45,7	52,9
	[%]	25	25	25
Exponent n	[Exp]	1,24	1,24	1,25
AF 6- Bijela boja RAL 9016	[KN]	2.811,00	2.863,00	2.907,00
CF - Boja po izboru	[KN]	3.374,00	3.436,00	3.488,00
SF	[KN]	3.655,00	3.722,00	3.779,00
CR	[KN]	7.509,00	8.141,00	8.773,00
Odgovarajući elekt. grijač	[Watt/A]	500 / 3	500 / 3	500 / 3

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$:

COBRATHERM CBT180 L/R

Visina 1820 mm

Model	CBT180 L/R		
	Visina H [mm]	1820	
Dubina T [mm]	58		
Dužina L [mm]	400	500	600
Oсно odstojanje N [mm]	50	50	50
$\Phi_S \Delta T 50K$ - Toplinski učinak [Watt]	586	702	811
Težina [kg]	10,3	12,0	13,6
Volumen [dm ³]	4,1	4,7	5,2
Standardni protok Q _{ms} [kg/h]	50,2	59,7	69,0
[%]	25	25	25
Exponet n [Exp]	1,24	1,25	1,26
AF 6- Bijela boja RAL 9016 [KN]	3.132,00	3.192,00	3.261,00
CF - Boja po izboru [KN]	3.758,00	3.831,00	3.914,00
SF [KN]	4.071,00	4.150,00	4.240,00
CROM [KN]	9.006,00	9.949,00	10.884,00
P _{el} /I Odgovarajući elekt.grijač [Watt/A]	500 / 3	500 / 3	800 / 4

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$: