


DECOSTAR DSV80

Visina 813 mm

DECOSTAR S UGRAĐENIM VENTILOM

| Model | | DSV80 | | |
|--|--------------------|-----------------|-----------------|-----------------|
| Visina H | [mm] | 813 | | |
| Dubina T | [mm] | 91 | | |
| Dužina L | [mm] | 500 | 600 | 750 |
| Oсно ostojanje pol/povrat N | [mm] | 50 | 50 | 50 |
| $\Phi_S \Delta T 50K$ | [Watt] | 424 | 495 | 601 |
| | [kg] | 8,9 | 10,6 | 13,1 |
| | [dm ³] | 2,5 | 3,0 | 3,8 |
| | [kg/h] | 28,5 | 34,1 | 42,7 |
| | [%] | 50 | 50 | 50 |
| Exponent n | [Exp] | 1,21 | 1,21 | 1,22 |
| AF - Bijela boja | [Kn] | 4.456,00 | 4.509,00 | 4.588,00 |
| CF - Boja po izboru | [Kn] | 5.348,00 | 5.411,00 | 5.505,00 |
| P _{el} /I odgovarajući grijač | [Watt/A] | 500 / 3 | 500 / 3 | 500 / 3 |

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

 $\Delta T 50K$:

DECOSTAR DSV125

Visina 1257 mm

DECOSTAR S UGRAĐENIM VENTILOM

| Model | | DSV125 | | |
|--|--------------------|-----------------|-----------------|-----------------|
| Visina H | [mm] | 1257 | | |
| Dubina T | [mm] | 91 | | |
| Dužina L | [mm] | 500 | 600 | 750 |
| Oсно ostojanje pol/povrat N | [mm] | 50 | 50 | 50 |
| $\Phi_S \Delta T 50K$ | [Watt] | 638 | 737 | 885 |
| | [kg] | 13,6 | 16,3 | 20,3 |
| | [dm ³] | 3,9 | 4,7 | 5,9 |
| | [kg/h] | 43,9 | 42,6 | 65,8 |
| | [%] | 50 | 50 | 50 |
| Exponent n | [Exp] | 1,23 | 1,23 | 1,23 |
| AF - Bijela boja | [Kn] | 5.218,00 | 5.302,00 | 5.429,00 |
| CF - Boja po izboru | [Kn] | 6.626,00 | 6.369,00 | 6.514,00 |
| P _{el} /I odgovarajući grijač | [Watt/A] | 500 / 3 | 500 / 3 | 800 / 4 |

 $\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

 $\Delta T 50K$:



DECOSTAR DSV150

Visina 1479 mm

DECOSTAR S UGRAĐENIM VENTILOM

| Model | | DSV150 | | |
|--------------------------------|--------------------|-----------------|-----------------|-----------------|
| Visina H | [mm] | 1479 | | |
| Dubina T | [mm] | 91 | | |
| Dužina L | [mm] | 500 | 600 | 750 |
| Oсно ostojanje pol/povrat N | [mm] | 50 | 50 | 50 |
| $\Phi_S \Delta T 50K$ | [Watt] | 738 | 846 | 1008 |
| | [kg] | 15,6 | 18,7 | 23,3 |
| | [dm ³] | 4,5 | 5,4 | 6,8 |
| | [kg/h] | 50,7 | 60,9 | 76,1 |
| | [%] | 50 | 50 | 50 |
| Exponent n | [Exp] | 1,24 | 1,24 | 1,24 |
| AF - Bijela boja | [Kn] | 5.881,00 | 5.980,00 | 6.130,00 |
| CF - Boja po izboru | [Kn] | 7.075,00 | 7.177,00 | 7.356,00 |
| P_{cl}/I odgovarajući grijač | [Watt/A] | 500 / 3 | 800 / 4 | 1100 / 5 |

$\Phi_S \Delta T 50K$: za temperaturni režim 75 / 65 / 20 °C ($\Delta T 50K$) (EN 442)

$\Delta T 50K$: